



**Specifications Ledvance LED  
Downlight Performance DN155 14W  
1500lm 65D - 830 Warm White |  
180mm - IP54**

[View Product](#)

## General Information

|                          |                                    |
|--------------------------|------------------------------------|
| SKU                      | 238962                             |
| EAN                      | 4058075459137                      |
| Brand                    | Ledvance                           |
| Manufacturer Name        | DL UGR19 DN155 PFM 14W/830 WT IP54 |
| Any Lamp all-in warranty | 5 Years                            |
| Average Lifetime (h)     | 70000                              |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Driver Included             | Yes               |
| Beam Angle (degree)         | 65                |

|                          |                                |
|--------------------------|--------------------------------|
| Luminous Efficacy (lm/W) | 108                            |
| Power factor             | >0.90                          |
| Installation Depth (mm)  | 100                            |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 155               |
| IP-rating              | IP54              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature  | -20 to +45        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Fixture Connection     | Screw terminal    |
| Series                 | DN155             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 65  |
| Diameter (mm) | 180 |

## Why Any-lamp?

## Sensor Information

 Type of sensor

Order from the **largest lighting specialist** in Europe

No Sensor

 **Customised** quotation



Up to **7 years warranty**



**Easy** return process