



Specifications Noxion LED Panel  
Louvre Excell Pronox 38W 4200lm -  
840 Cool White | 150x15cm - UGR 152  
- Dali Dimmable

[View Product](#)

General Information

|                          |                                                                      |
|--------------------------|----------------------------------------------------------------------|
| SKU                      | 235767                                                               |
| EAN                      | 8719157006590                                                        |
| Brand                    | Noxion                                                               |
| Manufacturer Name        | Noxion LED Louvre Excell G2. 38W 4000K 1500 Polish DALI (1x49W eqv.) |
| Any Lamp all-in warranty | 6 Years                                                              |
| Average Lifetime (h)     | 70000                                                                |
| Series                   | Louvre Excell                                                        |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Efficacy (lm/W)    | 110.5              |
| Suitable for Outdoor        | No                 |
| IP-rating                   | IP20               |

|                        |                                         |
|------------------------|-----------------------------------------|
| Impact Protection (IK) | IK02 - 0.20 joule                       |
| Fixture Connection     | Terminal, 2-pole (MAINS)   2-pole (DIM) |
| Finish of Reflector    | Gloss                                   |
| Driver Included        | Yes                                     |
| Power factor           | >0.90                                   |
| Product Type Category  | LED Panel                               |

## Fixture Information

|                       |                                  |
|-----------------------|----------------------------------|
| Mounting Method       | Recessed                         |
| Unified Glare Rating  | < 15 - for special applications  |
| Optical Cover         | PET (Polyethylene Terephthalate) |
| Operating Temperature | -20 to +50                       |
| Emergency Lighting    | No Emergency Unit                |
| Colour of the Fixture | White                            |
| Housing               | Steel                            |
| Colour of material    | White                            |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 150x15cm |
| Length (mm)    | 1495     |
| Width (mm)     | 150      |
| Height (mm)    | 55       |

## Why Any-lamp?

## Sensor Information


**Order from the largest lighting specialist in Europe**


**Customised quotation**


**Up to 7 years warranty**


**Easy return process**